

Girder Hangers

GTS & MGTS

Used to fix trusses, girders and rafters to the wall plate.

Girder Hangers are available in two different types:

Girder Hangers GTS


Mini GTS MGTS

- The GTS is for supporting Truss Rafters, fully adjustable for depths between 100 to 225mm.
- The TECO Mini GTS is for short span, mono or in-fill trusses 100mm deep.
- Tag on the base of the hangers help avoid rotation and aid fast, accurate location. The tag can easily be bent if not required.
- Increased bearing.




SPECIFICATION

- Galvanised steel EN 10346 DX51D Z275
- 1.2mm thick
- The GTS is tested by Lucideon Ltd.



GTS



GTS

INSTALLATION

- All holes should be nailed using 30 x 3.75 square twist nails or equivalent.

Code	Product	Product Dimensions (mm)			Characteristic Value (kN) for Eurocode 5	Safe Working Load for BS5268 (kN)			Box Qty.
		Width	Leg	Bearing		Short Term	Medium Term	Long Term	
Pre Galvanised Steel - 1.2mm									
GIRDER HANGER									
GTS38	Woody Girder Truss Shoe	38	300	85	17.45	8.73	8.31	7.27	50
GTS50	Woody Girder Truss Shoe	50	300	85	17.45	8.73	8.31	7.27	50
GTS63	Woody Girder Truss Shoe	63	300	85	17.45	8.73	8.31	7.27	25
GTS76	Woody Girder Truss Shoe	76	300	85	17.45	8.73	8.31	7.27	25
GTS100	Woody Girder Truss Shoe	100	300	85	17.45	8.73	8.31	7.27	25
MINI GTS									
MGTS38	Mini Girder Truss Shoe	38	100	85	-	-	-	-	25
MGTS50	Mini Girder Truss Shoe	50	100	85	-	-	-	-	25